

SILENCER®

Technical Specification Sheet

ROVER-R



- Brushless DC Motor (1 H.P.)
- Simultaneous Digital RPM and RCF Display
- Speed settable in RPM or RCF
- Digital Time Display
- Timer Range 1-999 plus Hold
- Save and recall up to three speed and time configurations
- Lock settings to prevent accidental changes
- Nine selectable Dynamic Braking Levels plus Off
- On error displays error number and an explanation of the error
- Completely enclosed rotor chamber
- High-strength alloy rotor chamber with drain
- See-through high-strength lid
- Dual Safety Interlock System – Ensures the lid is closed and locked
- Audible End-Of-Run Indicator Is User Settable From Off To Nine Beeps or Continuous
- Spill Resistant Control Panel
- Direct Drive System
- Microprocessor Control

Power Requirements 115v 60hz, 15 Amps

Dimensions 19.25"W x 21.5"D x 30.13"H

Weight 193lbs

Performance Specifications:

Speed Control +/- 2%

Timer +/- 5%

Maximum Noise Level 58 dBA



Proudly designed and manufactured in the great United States

COMPATIBLE ROTOR



ROVER-R Horizontal Rotor

Maximum speed	4,000 RPM
Maximum RCF	3,200 x g
Approximate acceleration	0 - Max RPM : 60 seconds
Approximate deceleration	Max - 0 RPM
	Brake On : 60 seconds
	Brake Off : 360 seconds