



#### S2510R Features

- Brushless DC Motor (1 H.P.)
- Simultaneous Digital RPM And RCF Display
- Speed Settable in RPM Or RCF
- Digital Time Display
- Digital Temperature Display
- Timer Range 1-999 Plus Hold
- Save And Recall Up To Three Speed And Time Configurations
- Lock Settings To Prevent Accidental Changes
- Nine Selectable Dynamic Braking Levels Plus Off
- On Error Displays Error Number And An Explanation Of The Error
- Completely Enclosed Rotor Chamber \*
- See-Through High-Strength Lid
- High-strength alloy rotor chamber with drain
- Dual Safety Interlock System – To Ensure The Lid Closed And Locked
- Audible End-Of-Run Indicator Is User Settable From Off To Nine Beeps Or Continuous
- Spill Resistant Control Panel
- Direct Drive System
- Microprocessor Control
- Ozone safe refrigeration system

\* Patented Feature

Power Requirements	115v 60hz, 15 Amps
Dimensions	31.00"W x 21.50"D x 16.25"H
Performance Specifications:	
Speed Control	+/- 2%
Timer	+/- 5%
Maximum Noise Level	58 dBA

- Maximum speed: - S2510R w/ Horizontal rotor 4,000 RPM
- Maximum RCF: - S2510R w/ Horizontal rotor 3,200 x g
- Approximate acceleration rate (0 - Max. RPM):  
- S2510R w/ Horizontal rotor 60 seconds
- Approximate deceleration rate (Max. - 0 RPM):  
- S2510R w/ Horizontal rotor (w/ Brake on) 60 seconds  
- Brake off 360 seconds

