

SILENCER®

Technical Specification Sheet

STEALTH



- Brushless DC Motor (1 H.P.)
- Simultaneous Digital RPM And RCF Display
- Speed settable in RPM Or RCF
- Digital Time Display
- Timer Range 1-999 Plus Hold
- Save and recall up to three speed and time configurations
- Lock settings to prevent accidental changes
- Nine selectable dynamic braking levels plus off
- On error displays error number and an explanation of the error
- Completely enclosed rotor chamber
- High-strength alloy rotor chamber
- See-through high-strength lid
- Dual Safety Interlock System – ensures the lid is closed and locked
- Audible End-Of-Run Indicator is user settable from off to nine beeps or continuous
- Spill Resistant Control Panel
- Direct Drive System
- Microprocessor Control

Power Requirements 115v 60hz, 5 Amps
Dimensions 15.6"W x 19"D x 13.75"H
Weight 65lbs

Performance Specifications:
Speed Control +/- 2%
Timer +/- 5%
Maximum Noise Level 58 dBA



Proudly designed and manufactured in the great United States

COMPATIBLE ROTOR



STEALTH Horizontal Rotor

Maximum speed		4,000 RPM
Maximum RCF		2,800 x g
Approximate acceleration	0 - Max RPM :	30 seconds
Approximate deceleration	Max - 0 RPM	
	Brake On :	30 seconds
	Brake Off :	360 seconds