

SILENCER®

Technical Specification Sheet

TANK



- Brushless DC Motor (1 H.P.)
- Simultaneous digital RPM and RCF display
- Speed settable in RPM Or RCF
- Digital Time Display
- Timer Range 1-999 plus hold
- Save and Recall up to three speed and time configurations
- Lock settings to prevent accidental changes
- Nine selectable Dynamic Braking Levels plus off
- On error displays error number and an explanation of the error
- Completely enclosed rotor chamber
- High-strength alloy rotor chamber
- See-through high-strength lid
- Dual Safety Interlock System – ensures the lid is closed and locked
- Audible End-Of-Run Indicator is user settable from off to nine beeps or continuous
- Spill Resistant Control Panel
- Direct Drive System
- Microprocessor Control

Power Requirements 115v 60hz, 10 Amps
Dimensions 19.25"W x 21.50"D x 14.38"H
Weight 96 lbs

Performance Specifications:
Speed Control +/- 2%
Timer +/- 5%
Maximum Noise Level 58 dBA



Proudly designed and manufactured in the great United States

COMPATIBLE ROTOR



TANK Horizontal Rotor

Maximum speed	4,000 RPM
Maximum RCF	3,200 x g
Approximate acceleration	0 - Max RPM : 60 seconds
Approximate deceleration	Max - 0 RPM :
	Brake On : 60 seconds
	Brake Off : 360 seconds