

SILENCER®

Technical Specification Sheet

S12V



- Maintenance Free
- Brushless DC Motor (1/2 H.P.)
- Four User Selectable Speed Settings
- Four User Selectable Time Settings
- Completely Enclosed Rotor Chamber
- See-Through High-Strength Lid

- Dual Safety Interlock System – To Ensure The Lid Closed And Locked
- Audible End-Of-Run Indicator
- Spill Resistant Control Panel
- Direct Drive System
- Microprocessor Control

Power Requirements 115v 60hz, 5 Amps
Dimensions 13"W X 16.5"D X 11.5"H
Weight 39lbs

Performance Specifications:

Speed Control +/- 2%
Timer +/- 5%
Maximum Noise Level 58 dBA



Proudly designed and manufactured in the great United States

COMPATIBLE ROTORS

S12V-F10 10x10ml 45° FA Rotor



Time Options	5, 7, 10, 15 minutes
Minimum speed	1,700 RPM
Maximum speed	4,500 RPM
Minimum RCF	437 x g
Maximum RCF	2,802 x g
Approximate acceleration	0 - Max RPM: 15 seconds
Approximate deceleration	Max - 0 RPM: 60 seconds

S12V-H8 8x10ml Horizontal Rotor



Time Options	5, 7, 10, 15 minutes
Minimum speed	1,700 RPM
Maximum speed	4,000 RPM
Minimum RCF	437 x g
Maximum RCF	2,418 x g
Approximate acceleration	0 - Max RPM: 15 seconds
Approximate deceleration	Max - 0 RPM: 45 seconds